



### MAIN FEATURES:

- Class-leading hydraulic efficiency
- Upgraded unitized mechanical seal
- ECM for simple variable speed control

### SPECIFICATIONS & REQUIREMENTS

<b>Pump Size</b>	6G
<b>Impeller Diameter</b>	11.375" (28.9 CM)
<b>Motor Power</b>	60 HP (44.7 kW)
<b>Motor Operation</b>	Single Speed

### GENERAL INFORMATION

<b>Rental Category</b>	Base Mounted Pump
<b>Pump Manufacturer</b>	Bell & Gossett
<b>Pump Model</b>	Series 1510
<b>Accessories Included</b>	None

### OUTPUT

<b>Design Head / Flow</b>	120' (36.6 M) / 1,340 GPM (5,072 LPM)
<b>Max Flow</b>	2,200 GPM (8,327 LPM)
<b>Head @ Max Flow</b>	72' (21.9 M)
<b>MAWP</b>	175 PSIG (12.1 BARG)

### DIMENSIONS

<b>Overall Length</b>	05' 00" (1.5 M)
<b>Overall Width</b>	02' 07" (0.8 M)
<b>Overall Height</b>	03' 00" (0.9 M)
<b>Shipping Weight</b>	1,750 LBS (794 KGS)

### CONNECTIONS

<b>Suction (Input)</b>	8" 125# FLG
<b>Discharge (Output)</b>	6" 125# FLG
<b>Voltage</b>	230 V (or 460 V) / 3 Phase / 60 Hz
<b>Amperage</b>	160 A (or 80 A)