



### MAIN FEATURES:

- Class-leading hydraulic efficiency
- Upgraded unitized mechanical seal
- ECM for simple variable speed control

### SPECIFICATIONS & REQUIREMENTS

<b>Pump Size</b>	6G
<b>Impeller Diameter</b>	12.875" (32.7 CM)
<b>Motor Power</b>	100 HP (75 kW)
<b>Motor Operation</b>	Variable Speed

### GENERAL INFORMATION

<b>Rental Category</b>	Base Mounted Pump
<b>Pump Manufacturer</b>	Bell & Gossett
<b>Pump Model</b>	Series e-1510
<b>Accessories Included</b>	None

### OUTPUT

<b>Design Head / Flow</b>	175' (53.3 M) / 1,000 GPM (3,785 LPM)
<b>Max Flow</b>	2,802 GPM (10,605 LPM)
<b>Head @ Max Flow</b>	85' (25.9 M)
<b>MAWP</b>	250 PSIG (17.2 BARG)

### DIMENSIONS

<b>Overall Length</b>	05' 10" (1.8 M)
<b>Overall Width</b>	06' 00" (1.8 M)
<b>Overall Height</b>	04' 06" (1.4 M)
<b>Shipping Weight</b>	2,400 LBS (1,089 KGS)

### CONNECTIONS

<b>Suction (Input)</b>	8" 250# FLG
<b>Discharge (Output)</b>	10" 250# FLG
<b>Voltage</b>	460 V / 3 Phase / 60 Hz
<b>Amperage</b>	125 A