



MAIN FEATURES:

- Frame-mounted Shell and Tube Heat Exchanger
- Steam to Hydronic Water Heat Transfer
- Pre-installed Steam Valving Ready for Use

GENERAL INFORMATION

Rental Category	Heat Exchanger
Unit Design	Skid-Mounted
Heat Exchanger Design	Shell and Tube
Use Type	Steam – Water, Water – Water

DIMENSIONS (Differ by Variant)

Overall Length	10' 10" / 15' 03" (3.3 / 4.6 M)
Overall Width	07' 00" / 09' 04" (2.1 / 2.8 M)
Overall Height	02' 09" / 02' 07" (0.8 / 0.8 M)
Shipping Weight	4,000 / 5,000 LBS (1,814 / 2,268 KGS)

SPECIFICATIONS & REQUIREMENTS

HX Surface Area	263 FT ² (24.4 M ²)
Design Pressure – Shell	150 PSIG (10.3 BARG)
Design Pressure – Tube	150 PSIG (10.3 BARG)
Max Flow – Shell	600 GPM (2,217 LPM)
Max Flow – Tube	800 GPM (3,028 LPM)

CONNECTIONS (Differ by Variant)

Steam (Input)	4" / 6" 150# FLG x 1
Condensate (Output)	2" NPT x 1
HHW Supply (Output)	6" / 8" 150# FLG x 1
HHW Return (Input)	6" / 8" 150# FLG x 1